


PUMP AND MOTOR DATA

n (rpm):	2900	Motor phase:	3~
Max working pressure (bar):	6	Un (V):	230/400
H max (m):	15.40	fn (Hz):	50
H min (m):	5.60	Poles:	2
Q min (mc/h):	3.60	In (A):	3.7 / 2.2
Q max (mc/h):	18.00	PF:	0.80
Pn (kW):	0.75	Insulation class:	F
Pn (HP):	1.00	Duty:	S1
Impeller diameter (mm):	113.00	Min liquid temperature (°C):	-10.00 °C
2nd impeller diameter (mm):	0.00	IE:	IE3-80.7
Motor type:	IM	Weight (kg):	20.700

MATERIALS

Pump Casing:	Cast iron GJL 200 EN 1561	Impeller:	Cast iron GJL 200 EN 1561
Suction Flange:	Cast iron GJL 200 EN 1561	Shaft:	Cr-Ni steel 1.4305 EN 10088 (AISI 303)
Lantern Bracket:	Cast iron GJL 200 EN 1561	Mechanical Seal:	Carbon-Ceramic-NBR



DIMENSIONS (MM)

dn1: G 1 1/2
dn2: G 1 1/2
a: 132.00 mm
m1: 100.00 mm
m2: 70.00 mm
n1: 190.00 mm
n2: 140.00 mm
b: 50.00 mm
s: 16
l1: 83.00 mm
l2: 89.00 mm
g1: 12.00 mm
h1: 208.00 mm
h2: 67.00 mm
w: 199.00 mm
fM: 393.00 mm

