


PUMP AND MOTOR DATA

n (rpm):	2800	Motor phase:	3~
H max (m):	30.00	Un (V):	230/400
H min (m):	15.00	fn (Hz):	50
Q min (mc/h):	2.00	Poles:	2
Q max (mc/h):	6.50	In (A):	2.8 / 1.6
Pn (kW):	0.55	PF:	0.80
Pn (HP):	0.75	Insulation class:	F
Impeller diameter (mm):	0.00	Duty:	S1
2nd impeller diameter (mm):	0.00	Weight (kg):	8.800
Motor type:	IM		

MATERIALS

Pump Casing:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Impeller:	Noryl PPO-GF20
Casing Cover:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Shaft:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)
Suction Casing:	Noryl PPO-GF20	Mechanical Seal:	Carbon-Ceramic-NBR
Stage Casing:	Noryl PPO-GF20		



DIMENSIONS (MM)

dn1: G 1
dn2: G 1
a: 115.00 mm
m1: 33.00 mm
m3: 8.00 mm
n1: 146.00 mm
n2: 112.00 mm
b: 30.00 mm
g1: 10.00 mm
h1: 116.00 mm
h2: 61.00 mm
w: 112.00 mm
w1: 112.00 mm
fM: 391.00 mm

