


PUMP AND MOTOR DATA

n (rpm):	2800	Un (V):	230
H max (m):	30.00	fn (Hz):	50
H min (m):	15.00	Poles:	2
Q min (mc/h):	2.00	In (A):	4.2
Q max (mc/h):	6.50	PF:	0.95
Pn (kW):	0.55	C (mF):	16
Pn (HP):	0.75	Vc (V):	450
Impeller diameter (mm):	0.00	Insulation class:	F
2nd impeller diameter (mm):	0.00	Duty:	S1
Motor type:	IM	Max liquid temperature (°C):	35
Motor phase:	1~	Weight (kg):	9.750

MATERIALS

Pump Casing:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Impeller:	Noryl PPO-GF20
Casing Cover:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Shaft:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)
Suction Casing:	Noryl PPO-GF20	Mechanical Seal:	Carbon-Ceramic-NBR
Stage Casing:	Noryl PPO-GF20		



DIMENSIONS (MM)

dn1: G 1
dn2: G 1
a: 115.00 mm
m1: 33.00 mm
m3: 8.00 mm
n1: 146.00 mm
n2: 112.00 mm
b: 30.00 mm
g1: 10.00 mm
h1: 116.00 mm
h2: 61.00 mm
w: 112.00 mm
w1: 112.00 mm
fM: 391.00 mm

